PERFORMANCE MADE SMARTER

2-wire level transmitter

5343B

- Potentiometer or Ohmic input
- Programmable sensor error value
- High measurement accuracy
- Unique process calibration function
- Programmable via standard PC

Application

- Conversion of resistance variation to standard analog current signals, e.g. from Ohmic level sensors or valve positions.
- User-defined linearization function can be activated.

Technical characteristics

- Within a few seconds the user can program PR5343B to measure within the defined Ohmic values.
- Continuous check of vital stored data for safety reasons.
- The transmitter is protected against polarity reversal.
- PR5343B is configured to the current task by way of a PC, the PReset software and the communications interface Loop Link.
- The PRelevel configuration tool included in the PReset software has been developed specifically for the configuration of level applications. Among other things, it contains a function for ”on line” measurement of input span as well as a linearization function for volume linear output from horizontal cylindrical tanks.

Mounting / installation

- For DIN form B sensor head or DIN rail mounting with a special fitting.
- NB: As I.S. / Ex barrier for 5343B we recommend 5104B, 5114B or 5116B.

Connections



This page is automatically generated on the basis of information provided on www.prelectronics.com and affiliated websites. It is provided to you as a service and for information purpose only. While we have attempted to maintain the information as accurately as possible, the page may contain errors or omissions for which we disclaim any and all liability

Order:

Type
5343B

Environmental Conditions

Specifications range	-40°C to +85°C
Calibration temperature	20...28°C
Relative humidity	< 95% RH (non-cond.)
Protection degree (encl./terminal)	IP68 / IP00

Mechanical specifications

Dimensions	Ø 44 x 20.2 mm
Weight approx.	50 g
Wire size	1 x 1.5 mm^2 stranded wire
Screw terminal torque	0.4 Nm
Vibration	IEC 60068-2-6 : 2007
Vibration: 2...25 Hz	±1.6 mm
Vibration: 25...100 Hz	±4 g

Common specifications

Supply voltage	8.0...30 VDC
Internal consumption	25 mW…0.8 W
Voltage drop	8.0 VDC
Warm-up time	5 min.
Communications interface	Loop Link
Signal / noise ratio	Min. 60 dB
Response time (programmable)	0.33...60 s
Accuracy	Better than 0.1% of selected range
Signal dynamics, input	19 bit
Signal dynamics, output	16 bit
Effect of supply voltage change	< 0.005% of span / VDC
EMC immunity influence	< ±0.5% of span

Input specifications

Max. offset	50% of selected max. value
Linear resistance input: Measurement range / min. range (span)	0...100 kΩ / 1 kΩ
Min. measurement range	1 kΩ
Cable resistance per wire (max.), lin. R	100 Ω
Sensor current, lin. R	> 25 µA, < 120 µA
Effect of sensor cable resistance (3-wire), lin R	< 0.002 Ω / Ω
Sensor error detection, lin. R	Yes

Output specifications

Current output: Signal range	4…20 mA
Min. signal range	16 mA
Updating time	135 ms
Load resistance, current output	≤ (Vsupply - 8) / 0.023 [Ω]
Load stability, current output	≤0.01% of span / 100 Ω
Sensor error indication, current output	Programmable 3.5…23 mA
NAMUR NE 43 Upscale/Downscale	23 mA / 3.5 mA
*of span	= of the presently selected range

Approvals

EMC	EN 61326-1
ATEX 2004/108/EC	KEMA 03ATEX1538
FM	2D5A7
IECEx	DEK 13.0036X
INMETRO	DEKRA 13.0002 X
EAC TR-CU 020/2011	EN 61326-1
EAC Ex TR-CU 012/2011	RU C-DK.GB08.V.00410
DNV Marine	Stand. f. Certific. No. 2.4
GL	V1-7-2