

## 2-wire programmable transmitter

### 5131B

- Input for RTD, TC, mV, linear resistance, mA, and V
- 3.75 kVAC galvanic isolation
- 4...20 mA loop output
- 1- and 2-channel versions
- ATEX Ex / I.S. version
- DIN rail mounting



#### Advanced features

- The 5131 transmitter can be configured with a standard PC and the Loop Link communications unit.


#### Application

- Independent channel jumper selectable inputs for current/voltage or temperature.
- Current input programmable in range the 0...100 mA and voltage inputs in the range 0...250 VDC.
- Linearized, electronic temperature measurement with RTD or TC sensor.
- Conversion of linear resistance variation to a standard analog current / voltage signal, for example from solenoids and butterfly valves or linear movements with attached potentiometer.
- 4- or 3-wire connection with automatic cable compensation or 2-wire connection with programmable cable compensation.
- Configurable sensor error detection including NAMUR NE43.

#### Technical characteristics

- Programming can be performed with or without a power supply.
- The 2-channel version has full galvanic isolation between the channels.
- Separation of circuits in PELV/SELV installations.
- I.S. barrier for temperature sensors, potentiometers and current / voltage signals.

#### Connections



**Order:**

Type	Input	Channels
5131B	RTD / TC / mV / R	: 1 Single : A
	mA / V / mV	: 2 Double : B
	Channel 1, RTD / TC / mV / R	: 3
	Channel 2, mA / V / mV	

\***Note!** For TC inputs with internal CJC, remember to order CJC connectors type 5910Ex (ch. 1) and 5913Ex (ch. 2).

**Environmental Conditions**

Specifications range.....	-20°C to +60°C
Calibration temperature.....	20...28°C
Relative humidity.....	< 95% RH (non-cond.)
Protection degree.....	IP20

**Mechanical specifications**

Dimensions (HxWxD).....	109 x 23.5 x 130 mm
Weight approx.....	195 g
DIN rail type.....	DIN 46277
Wire size.....	1 x 2.5 mm <sup>2</sup> stranded wire
Screw terminal torque.....	0.5 Nm

**Common specifications**

Supply voltage.....	7.5...35 VDC
Fuse.....	50 mA SB / 250 VAC
Isolation voltage, test / working.....	3.75 kVAC / 250 VAC
Communications interface.....	Loop Link
Signal / noise ratio.....	Min. 60 dB (0...100 kHz)
Response time (0...90%, 100...10%):	
Temperature input (programmable).....	400 ms...60 s
mA / V input (programmable).....	250 ms...60 s
Updating time.....	115 ms (temperature input)
Updating time.....	75 ms (mA / V / mV input)
Signal dynamics, input.....	22 bit
Signal dynamics, output.....	16 bit
Effect of supply voltage change.....	< 0.005% of span / VDC
EMC immunity influence.....	< ±0.5% of span
Extended EMC immunity: NAMUR	
NE 21, A criterion, burst.....	< ±1% of span

**Input specifications**

Max. offset.....	50% of selected max. value
RTD input.....	Pt100, Ni100, lin. R
Cable resistance per wire (max.), RTD.....	10 Ω
Sensor current, RTD.....	Nom. 0.2 mA
Effect of sensor cable resistance (3-/4-wire), RTD.....	< 0.002 Ω / Ω
Sensor error detection, RTD.....	Yes
TC input: Thermocouple type.....	B, E, J, K, L, N, R, S, T, U, W3, W5, LR
Cold junction compensation (CJC).....	< ±1.0°C
Sensor error current, TC.....	Nom. 30 µA
Sensor error detection, TC.....	Yes
Current input: Measurement range.....	0...100 mA
Min. measurement range (span), current input.....	4 mA
Input resistance: Supplied unit.....	Nom. 10 Ω + PTC 10 Ω
Input resistance: Non-supplied unit.....	RSHUNT = ∞, VDROPO < 6 V
Voltage input: Measurement range.....	0...250 VDC
Voltage input: Measurement range.....	-150...+150 mV
Min. measurement range (span), voltage input.....	5 mV
Input resistance, voltage input.....	Nom. 10 MΩ (≤ 2.5 VDC)
Input resistance, voltage input.....	Nom. 5 MΩ (> 2.5 VDC)

Input resistance, voltage input..... Nom. 10 MΩ (mV input)

**Output specifications**

Max. offset.....	50% of selected max. value
Current output: Signal range.....	4...20 mA
Min. signal range.....	10 mA
Load resistance, current output.....	≤ (Vsupply - 7.5)/0.023 [Ω]
Load stability, current output.....	≤ 0.01% of span / 100 Ω
Current limit.....	≤ 28 mA
Sensor error indication, current output.....	Programmable 3.5...23 mA
NAMUR NE 43 Upscale/Downscale.....	23 mA / 3.5 mA
*of span.....	= of the presently selected range

**Approvals**

EMC.....	EN 61326-1
LVD 2006/95/EC.....	EN 61010-1
PELV/SELV.....	IEC 364-4-41 and EN 60742
ATEX 2004/108/EC.....	DEMKO 99ATEX124572
EAC TR-CU 020/2011.....	EN 61326-1
EAC Ex TR-CU 012/2011.....	RU C-DK.GB08.V.00410